



When image experience matters.

LUX70

Specification

Detail

Product Name	LUX70
Screen Size	70 in. (diagonal)
Orientation	Landscape/Portrait
Recommended Usage	24/7
Aspect Ratio	16:9
Brightness (typ)	700 nits
Backlight	Edge-Lit LED
Contrast Ratio (typ)	5000:1
Response Time (typ)	4 ms
Frame Rate	120Hz
Viewing Angle (typ)	176H,V
Native Resolution	Full HD 1920 x 1080 (1080p)
Display Color	>1 billion colors. Full 10 bit data path
Surface Treatment	None
Control and Monitoring	RS232/LAN with SNMP
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	300W
External Connections	DisplayPort, HDMI, VGA
Operating Temperature	0°F to + 104°F (0°C to + 40°C)
Storage and Transport Temperature	-4°F to + 140°F (-20°C to + 60°C)
Humidity	20 to 90% RH
Cabinet Dimensions (W x H x D)	62.2" x 36.2" x 3.0" (1581mm x 920mm x 77mm)
Bezel Width	1.1" (27 mm)
Weight	133 lbs (60 kg)
Weight (Shipping)	173 lbs (78 kg)
Touch Technology	N/A
OS Compatibility	N/A
Bezel color	Black
Mounting	Planar Profile Mounting System or VESA: 400 x 400 mm; 4 holes
Approvals	FCC Class A, EN60950, CE
Warranty	3 years Advance Exchange

Other Features

Integrated media player storage with AC power, redundant power supply, compatible with Planar Profile mounting system or UltraLux free-standing pedestals

UPC

8 10689 07182 2

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 7/15/2013

(c)Copyright 2013 Planar Systems, Inc. All rights reserved